ATTACHABLE DUCT COLLAR

ATTACHABLE DUCT COLLAR WITH SEGMENTED RINGS

Features and technical data:

- waterproof concrete stress class 1, stress class 2
- DIN 18533 W1.1-E, W1.2-E, W2.1-E
- gas-tight and watertight up to 1 bar
- one component for three or five different pipe diameters
- for radial and axial movement
- flexible connection of pipes to core drill hole
- including stainless steel attachment elements
- for installation on earth side
- sealing collar made of EPDM
- jubilee clips made of stainless steel A2 (AISI 304L) 20 mm wide
- attachment ring in stainless steel A2 (AISI 304L)
- segmented ring technology
- axial distance ADM 150: 340 mm
- axial distance ADM 200: 390 mm
- attachment elements including sealing ring



ADM attachment duct collar segment sections



attachment duct collar ADM200 1x90/110/125/140/160



Press seals for pipes

ATTACHABLE DUCT COLLAR

ADM						
Figure	Application range for carrier pipe OD (mm)	Article code	Article number	GTIN		
Core drill hole/wall sleeve ID max. 100 mm						
6	75 – 110	ADM150 75/90/110	1400060150	4052487127530		
Core drill hole/wall sleeve ID max. 200 mm						
6	90 – 160	ADM200 90/110/125/140/160	1400061200	4052487126526		

ACCESSORIES					
Figure	Article code	Article number	GTIN		
290 ml cartridge, colour grey elastic sealant to optimise wall surface in combination with sealing flanges					
ESS SECTION AND ADDRESS OF THE PARTY OF THE	EGO MS805	0505071623	4052487183772		