

Always. Reliable. Tight.

Standard press seal for building connections

HSD100 EW 1x24-44+4x7-12 b40 A2/EPDM55

Article no.: 3030300054, GTIN: 4052487126250



- **optical and tangible installation security due to integrated control opening**

- **Integrated segmented ring technology for individual adjustment to cable diameters on site**

For sealing a water line or a power cable and communications lines in core drills or wall sleeves.



Picture may differ from selected product

FACTS

Application range:

- DIN 18533 W1.1-E, DIN 18533 W1.2-E, DIN 18533 W2.1-E, DIN 18533 W2.2-E
- Waterproof concrete stress class 1, Waterproof concrete stress class 2

Advantages:

- Available from stock

Dimensions:

- Sealing width: 40 mm
- For core drills/wall sleeves \varnothing : 100 mm
- For 5 cables/pipes of which 4 x \varnothing 7-12 mm and 1 x \varnothing 24-44 mm

Properties:

- U-profile: maximum stability for press segments

Material:

- Press plates, screws and nuts: rust-free stainless steel V2A (AISI 304L)
- Rubber: EPDM

Tightness:

- Gastight and watertight

FEATURES

Wall sleeve/core drilled hole ID (mm):	100
Number of cables overall:	5
Number of cables:	4
Cable diameter:	7-12
Number of cables:	1
Cable diameter:	24-44

PICTURES

